

MSDS Report

Prepared For:G.G. TelecomAddress:120 J-Aurèle-Roux Victoriaville, Quebec CANADA, G6T 0N5Product Name:Li-ion BatteryModel:HSCNominal Voltage:14.8VRated Capacity:1800mAh, 26.64WhWeight:254.7gDimension:121.5mm×105.0mm×26.2mm (LxWxT)Prepared By:Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.Report No.:TCT180723M006			
Product Name: Li-ion Battery Model: HSC Nominal Voltage: 14.8V Rated Capacity: 1800mAh, 26.64Wh Weight: 254.7g Dimension: 121.5mm×105.0mm×26.2mm (L×W×T) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Prepared For:	G.G. Telecom	
Model: HSC Nominal Voltage: 14.8V Rated Capacity: 1800mAh, 26.64Wh Weight: 254.7g Dimension: 121.5mm×105.0mm×26.2mm (L×W×T) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Address:	120 J-Aurèle-Roux Victoriaville, Quebec CANADA, G6T 0N5	
Nominal Voltage: 14.8V Rated Capacity: 1800mAh, 26.64Wh Weight: 254.7g Dimension: 121.5mm×105.0mm×26.2mm (LxWxT) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Product Name:	Li-ion Battery	
Rated Capacity: 1800mAh, 26.64Wh Weight: 254.7g 121.5mm×105.0mm×26.2mm (L×W×T) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Model :	HSC	
Weight: 254.7g Dimension: 121.5mm×105.0mm×26.2mm (L×W×T) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Nominal Voltage:	14.8V	
Dimension: 121.5mm×105.0mm×26.2mm (L×W×T) Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Rated Capacity:	1800mAh, 26.64Wh	
Shenzhen TCT Testing Technology Co., Ltd. 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Weight:	254.7g	
Prepared By: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China.	Dimension :	121.5mm×105.0mm×26.2mm (L×W×T)	
Report No.: TCT180723M006	Prepared By :	1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong,	
	Report No.:	TCT180723M006	

Written by: Summer Yang

Approved by:

Inspected by:

Date:

Page 1



Section 1- Chemical Product & Company Identification			
Product Name:	Li-ion Battery	3	
Manufacture:	G.G. Telecom		
Address:	120 J-Aurèle-Roux Victoriaville, C	Quebec CANADA, G6	ST 0N5
Contact Person:	Jimmy Angers		
Tel:	+1-888-779-7646		
Fax:	+1-819-751-7000	(C)	
Emergency Tel:	+1-888-779-7646		
E-mail:	jangers@spypoint.com	<u>(1)</u>	
Item Code:	TCT180723M006		

Section 2- Hazards Identification		
Classification of Danger	See section 14.	
Primary Route(s) of Exposure	Eye, skin contact, ingestion.	
Health Hazard	The batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's risk of rupture, fire, heat, leakage of internal components, with could cause casualty loss. Abuses include but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.	

Report No.: TCT180723M006 Page 2 of 8 Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Section 3- Composition/Information on Ingredients			
Chemical Name	Concentration or concentration ranges (%)	CAS Number	
Lithium Cobalt Oxide (CoLiO ₂)	30-60	12190-79-3	
Graphite	10-30	7782-42-5	
Phosphate(1-), hexafluoro-, lithium	10-30	21324-40-3	
Copper	5-10	7440-50-8	
Aluminum foil	1-5	7429-90-5	
Nickel	1-5	7440-02-0	
PVC (Chloroethylene, polymer)	1-5	9002-86-2	

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First	st Aid Measures
Eye	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

Section 5- Fire Fighting Measures		
Characteristics of Hazard	Dusts at sufficient concentrations can form explosive mixtures with air. Combustion generates toxic fumes.	
Hazardous Combustion Products	Carbon dioxide.	

Report No.: TCT180723M006 Page 3 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Fire-extinguishing Methods and Extinguishing Media	For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.
Attention in Fire-extinguishing	Wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Meas	ures
Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7- Handling and Storage		
Handling	In case of rupture. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection equipment.	
Storage	Store in a cool, dry, well-ventilated area away from incompatible substances. Store locked up. Keep out of the reach of children.	
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.	

Report No.: TCT180723M006 Page 4 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Section 8 - Exposure Controls/Personal Protection		
Engineering Controls	Use adequate ventilation to keep airborne concentrations low. If used under conditions that generate particulates, the ACGIH TLV-TWA of 3mg/m³ respirable fraction (10mg/m³ total) should be observed.	
	Eye and Face Protection: None required for consumer use. If there is a risk of contact: Tight sealing safety goggles. Face protection shield.	
Personal Protective Equipment	Skin and Body Protection: None required for consumer use. If there is a risk of contact: Wear protective gloves and protective clothing.	
	Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.	

Section 9- Physical and Chemical Properties		
/	Appearance: Prismatic	0
Physical State	Color: Black	
	Odour: If leaking, smells of medical ether.	
Change in condit	tion	
рН	Not applicable as supplied.	
Flash Point	Not applicable unless individual components exposed.	K
Flammability	Not applicable unless individual components exposed.	
Relative density:	Not applicable unless individual components exposed.	
Solubility (water)	Not applicable unless individual components exposed.	
Solubility (other)	Not applicable unless individual components exposed.	

Section 10 – Stability and Reactivity		
Chemical Stability	Stable under recommended storage conditions.	
Possibility of Hazardous Reactions	None under normal processing.	
Conditions to Avoid	Exposure to air or moisture over prolonged periods.	

Report No.: TCT180723M006 Page 5 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Incompatible materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 – Toxicological Informati	ion
Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitization	Not Available.
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12-Ecological Information	
General note:	Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impact/ ecotoxicity	Not Available.

Section 13 – Disposal Considerations	
Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.
Attention for Waste Treatment	Deserted batteries couldn't be treated as ordinary trash. Couldn't be thrown into fire or placed in high temperature. Couldn't be dissected, pierced, crushed or treated similarly. Best way is recycling.

Section 14 – Transport I	nformation	
UN number	3480 & 3481	
Proper shipping name	Lithium ion batteries (limited to a maximum of 30% SoC) or; Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).	
Class or division	9	

Report No.: TCT180723M006 Page 6 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com



Marine pollutant (Yes/No)	No	
Label(s) / Placard Required	Miscellaneous Lithium batt	
Special precautions which a connection with transport or connection		
ICAO / IATA:	Organization (ICAO), TI or Inter (IATA), DGR Packing Instruction	dance with International Civil Aviation rnational Air Transport Association ns (PI) 965 Section II/Section IB, PI966 appropriate of IATA DGR 59th (2018
IMDG CODE:	The batteries are not restricted to IMDG Code 2016 Edition (Amdt 38-16) according to special provision 188.	
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.	
ADR/ ADN:	Economic Commission for Euro	the provisions of United Nations ope (UNECE) ADR/ADN if they meet the on 188 of Chapter 3.3. Applicable as from

Section 15 - Regulatory Information

Dangerous Goods Regulations

Recommendations on the Transport of Dangerous Goods-Model Regulations (20th revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2016 Edition Amdt 38-16)

Technical Instructions for the Safe Transport of Dangerous Goods

tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Classification and code of dangerous goods (GB 6944-2012)


2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Report No.: TCT180723M006 Page 7 of 8
Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





Section 16 – Additional Information

MSDS creation date: 2018 Version: 2.0

Sample photo:



To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Report No.: TCT180723M006

Shenzhen TCT Testing Technology Co., Ltd.

1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

Search Number: TCT180723M006C

Search System: http://www.tct-lab.com/cn/search.asp

Page 8 of 8